

## MP52 E2 Teams Datasheet

#### **Microsoft Phone MP52 E2**

A cost-effective basic Teams phone with high performance, the Android 13.0 OS-based Yealink MP52 E2 is plentiful in practical functions and outstanding in calling experience. The design of a non-touchscreen with physical navigation buttons makes the phone suitable for the common area and best migration practice from Skype for Business to Teams. Powered by Microsoft, MP52 E2 delivers a consistent Teams calling and meeting experience and improves productivity in daily work.



## **Key Features and Benefits**

#### **Excellent Calling Experience**

The Yealink MP52 E2 leverages the advantage of Yealink Optima HD voice and Noise Proof Technology. The full-duplex hands-free speakerphone with AEC & HAC handset gives the phone a high performance with crystal-clear sound and keeps each calling process stably and smoothly.

#### **Common Area Phone**

In common areas, such as in school/hospital/business scenarios, the Yealink MP52 E2 is invulnerable to damage caused by the design of non-touchscreen and physical buttons. Moreover, the appearance of a reasonable panel structure and fewer buttons would be appropriate for deploying the phone in the common area. Users can connect compatible USB headsets through the USB type-A port.

## **Efficient Management**

Effectively, MP52 E2 offers an auto-provisioning mechanism with phone development and configuration. Managers also can deploy, manage, and update the MP52 E2 phone in a variety of flexible ways, which include Microsoft and Yealink device management platforms.



- Android 13.0
- 2.4 inch (320 x 240) Non-touch Color Screen
- Optimal HD audio, Yealink Noise Proof Technology
- Magnet Handset
- USB Type-A port, Supports USB Headset
- Microsoft Teams-tailored APP
- Dual-port Gigabit Ethernet Switch, Supports PoE
- Supports Microsoft and Yealink device management platforms
- Wall mountable

# **Technical Specifications**

Specifications	Introduction
Audio Features	HD voice: HD handset, HD speaker
	Hearing aid compatible (HAC) handset, magnet handset
	Yealink Noise Proof Technology
	<ul> <li>Audio codec: SILK, G.722, G.722.1, G.722.1C, G.711 (A/μ), G.723, G.726, G.729AB,</li> <li>iLBC</li> </ul>
	Full-duplex hands-free speakerphone with AEC
	• VAD, CNG, AEC, PLC, AJB, AGC
Phone Features	Incoming/Outgoing P2P call
	Cloud PSTN call
	Call controls
	- Call hold/Call mute/Call transfer/Call forward
	- Visual voicemail
	- Synchronized call logs
	<ul> <li>Meeting call controls</li> <li>Mute/unmute, hold/resume</li> </ul>
	- Hang up
	- Add/remove participant
	Sign in with user credentials
	Sign in via website
	Phone lock/unlock
	Emergency calls
	Accessibility
	Power saving
	Common Area Phone (CAP)



Display and Indicator	<ul> <li>Color screen with backlight: 2.4 inches (320 x 240) non-touch Screen</li> <li>Multi-language user interface</li> <li>Power LED for call and message waiting indication</li> <li>Presence status control: available, busy, DND, be right back, off work, appear away</li> <li>Transfer button</li> <li>Time display</li> </ul>
Interface	<ul> <li>Dual-port Gigabit Ethernet, Supports PoE</li> <li>Power over Ethernet (IEEE 802.3af), class 3</li> <li>1 x USB Type-A port <ul> <li>USB headsets</li> <li>USB flash drive</li> </ul> </li> <li>1 x Security lock port</li> <li>1 x RJ9 (4P4C) handset port</li> <li>1 x RJ9 (4P4C) headset port</li> </ul>
Management	<ul> <li>Configuration: Browser/Phone/Auto Provisioning and Device Management Platform</li> <li>Provisioning priority management</li> <li>Auto Provisioning via Activation Code</li> <li>Yealink Redirection and Provisioning Service (RPS)</li> <li>QoE (Monitoring Reports)</li> <li>Reset to factory, reboot</li> <li>Package tracing export, system log</li> <li>Screenshot via URL</li> <li>Supports Microsoft Device Management Platform</li> <li>Supports Yealink Device Management Platform (YMDP/YMCS)</li> <li>Supports Unify Square Device Management Platform</li> <li>Simple Certificate Enrollment Protocol (SCEP)</li> </ul>
Network and Security	<ul> <li>IPv4/IPv6</li> <li>IP Assignment: Static/DHCP</li> <li>Proxy mode</li> <li>HTTP/HTTPS web server</li> <li>Time and date synchronization using SNTP</li> <li>Transport Layer Security (TLS)</li> <li>HTTPS certificate manager</li> <li>IEEE802.1X</li> <li>AES encryption for configuration file</li> </ul>



Other Physical Features	<ul> <li>Color: Classic Grey</li> <li>External Yealink AC adapter (optional): AC 100-240 V input and DC 5 V/2 A output</li> <li>USB output currency: 5 V/500 mA</li> <li>Power consumption (PSU): 1.5-4.5 W</li> <li>Power consumption (PoE): 2.3-6.0 W</li> <li>Dimension (W × D × H × T): 212 × 186 × 146 × 42 mm</li> <li>Operating humidity: 10-95%</li> <li>Operating temperature: -10-50°C (+14~122°F)</li> </ul>
Package Features	<ul> <li>Package content: <ul> <li>Yealink MP52 E2 IP phone</li> <li>Handset with handset cord</li> <li>Ethernet Cable (2m)</li> <li>Stand</li> <li>Quick Start Guide</li> <li>Power Adapter (Optional)</li> </ul> </li> <li>Qty/CTN: 10 PCS</li> <li>N.W/CTN: 10.7 kg</li> <li>G.W/CTN: 11.6 kg</li> <li>Giftbox size: 238 × 210 × 103 mm</li> <li>Carton Meas: 535 × 443 × 250 mm</li> </ul>

4